FRONT EMBLEM KIT							
CODE	(BLACK / LARGE) 799-4810000	(SILVER / SMALL) 799-4810100					
APPLICATION	Z900RS / SE (ZR900C / K) *CAFE not usable.						

•Thank you for purchasing Kitaco product. Read and understand the instruction before installing.

## **ATTENTION (MUST READ)**

- •This product is for dress-up. Do not use for other purposes.
- •This product is designed and made exclusive for Z900RS / SE (ZR900C / K), do not use other models. Do not modify the way which is not listed or it will cause damage and trouble.
- •We are not responsible for violation of law or damages and accidents caused by assembling mistake and improper setting.
- Please ask authorized mechanic for assembling and setting. Ask a specialist at specialty shop if you do not understand the role of the surrounding parts.
- •Refer to the manufacturer service manual when installation.
- •Bolts and nuts may get loosen by engine vibration. Make sure not to loosen any bolts and nuts before driving.
- •This instruction sheet is for the instruction for stock condition.
- × Metal/resin/alumite products get discolored/rust for ages as well as how to use. Please understand when using.

PACKING LIST					SILVER	
FIGURE	NAME		CODE	QTY		REMARK
1	FORK COVER (BLACK)	kawasaki EMBLEM	799-9000401	x1	-	
2	FORK COVER (SILVER)	kawasaki EMBLEM	799-9000402	-	x1	
3	STAY	EMBLEM	799-4810001	x1	x1	
4	WELNUT	C-550L(M5-P0.8)		x2	x2	
5	PAN HEAD SMALL SCREW	M5x25	053-0511025	x2	x2	
6	FLANGE HEXAGON BOLT	M6x15	062-0569015	x2	x2	TORQUE : 12N·m

## HOW TO INSTALL

•Remove optical axis adjustment stock socket bolt. (Refer to the illustration.)

- Tighten emblem stay with flange hexagon bolt together. (Refer to the illustration.)
- •Install emblem to stay with welnut / pan head screw.

• Make sure not to loosen any parts before riding.





Remove stock socket bolt x2 







